



Product Manual





The Tin Knocker 2n1 Crimper Beader is a lightweight machine that can perform both beading and crimping. This manual, hand-cranked machine is portable and works great in the field for the insulation trade where light gauge materials are used.


Features

- Performs both beading and crimping operations with one setup
- •No tools needed for setup
- •Both bead and crimp have markable surfaces to assist the operator in repeating setups
- •Either ½ inch or ¼ inch bead sizes are available
- •The unit allows the head to be positioned according to operator preferences
- •Easily portable for job site use




SPECIFICATIONS				
Maximum material thickness	0.030 inches			
Maximum crimp width	1-1/2 inches			
Bead diameter outside, large bead	1/4 inch			
Bead diameter outside, small bead	1/8 inch			
Maximum distance from bead center to edge	1-1/2 inches			
Benchtop mounting thickness range	3/4 to 3-1/2 inches			
Product dimensions	Approx. 26"x16"x12"			
Shipping weight	28 pounds			




















Ref. Letter	Qty.	Part No.	Description
1	2	2N1CB001	Depth adjustment knob
2	1	2N1CB002	Main driveshaft
3	2	2N1CB003	Gear mounting plate
4	2	2N1CB004	Drive gear
5	1	2N1CB005	Crimp and bead roller (male)
6	1	2N1CB006	Crimp and bead roller (female)





Ref. Letter	Qty.	Part No.	Description
7	1	2N1CB007	Top adjustment knob mounting plate
8	2	2N1CB008	Guide adjustment knob
9	1	2N1CB009	Bottom adjustment knob mounting plate
10	1	2N1CB010	Rotation position adjustment knob
11	1	2N1CB011	Main body and shaft (see p.4)
12	1	2N1CB012	Puck assembly (see p.5)
13	1	2N1CB013	Crank handle (see p.5)



TAAG Industries Corp.
"The TIN KNOCKER People"
1550 Simpson Way, Escondido, CA 92029
Tel: (800) 640-0746, Fax: (760) 727-9948

Email: info@taagind.com
www.tinknocker.com