

## WEV 15-150 HT (600563420) Angle grinder **Cardboard box**

Order no. 600563420 EAN 4007430320353



Representative picture











- · Optimum processing of stone: robust, powerful angle grinder with gear reduction and reduced, adjustable speed for material-friendly working
- Longer service life, more drive: the Metabo Marathon-Motor with patented dust guard, up to 20% more high overload capacity and 50% more torque
- Vario-Tacho-Constamatic (VTC)-Full Wave Electronics with Thumbwheel: for working at customized speeds to suit the application material and speeds that remain almost constant, even under load
- Tool-free adjustable guard; twist-proof
- Metabo S-automatic Torque Limiting Clutch: minimises kick-back to the lowest level when the disc jams unexpectedly for maximum user protection and swift progress
- Electronic overload protection, soft start and restart protection
- Gear housing can be mounted turned in 90° steps for left-handed operation or cutting
- Auto-stop carbon brushes to protect the motor

www.metabo.com 1/2



Technical values		
Parameters		
Amps	13.5 AMPS	
Grinding wheel Ø	6 "	
Rated input power	1550 W	
Output power	900 W	
No-load speed	2000 - 7600 RPM	
Revolutions at rated load	7600 RPM	
Torque	44 in-lbs	
Spindle thread	5/8" - 11 UNC	
Weight (without power cable)	5.7 lbs	
Cable length	8 ft	
Vibration		
Surface grinding	4.7 m/s <sup>2</sup>	
Uncertainty of measurement K	1.5 m/s <sup>2</sup>	
Polishing	2.5 m/s <sup>2</sup>	
Uncertainty of measurement K	1.5 m/s <sup>2</sup>	
Grinding with sandpaper	2.5 m/s <sup>2</sup>	
Uncertainty of measurement K	1.5 m/s <sup>2</sup>	
Noise emission		
Sound pressure level	93 dB(A)	
Sound power level (LwA)	104 dB(A)	
Uncertainty of measurement K	3 dB(A)	

## Scope of delivery

Guard

Inner support flange

Nut with two holes

Side Handle

Spanner wrench

www.metabo.com 2/2