

Headed Anchors & Shear Connectors



- Standard material– low carbon steel (ASTM A108).
- Stainless and aluminum are also available.
- Length is before weld.
- Stud diameters under 1/2" will be approximately 1/8" shorter after weld.
- Stud diameters 5/8" to 7/8" will be approximately 3/16" shorter after weld.
- Stud diameters 1" will be approximately 1/4" shorter after weld.

Standard Sizes

Headed Concrete Anchors

Shear Connectors

1/4 x 2-11/16"	1/2 x 1-5/8"	5/8 x 2-11/16"	3/4 x 3-3/16"	3/4 x 8-3/16"	7/8 x 7-3/16"
1/4 x 4-1/8"	1/2 x 2-1/8"	5/8 x 4-3/16"	3/4 x 3-3/8"	3/4 x 9-3/16"	7/8 x 9-3/16"
	1/2 x 2-5/8"	5/8 x 5-3/16"	3/4 x 3-7/8"	3/4 x 10-3/16"	7/8 x 10-3/16"
3/8 x 1-3/8"	1/2 x 3-1/8"	5/8 x 6-9/16"	3/4 x 4-3/16"	3/4 x 12-3/16"	
3/8 x 1-5/8"	1/2 x 4-1/8"	5/8 x 8-3/16"	3/4 x 4-3/8"		1 x 4-1/4"
3/8 x 2-5/8"	1/2 x 5-5/16"	5/8 x 10-3/16"	3/4 x 4-7/8"	7/8 x 3-3/16"	1 x 5-1/4"
3/8 x 3-1/8"	1/2 x 6-1/8"		3/4 x 5-3/16"	7/8 x 3-11/16"	1 x 6-1/4"
3/8 x 4-1/8"	1/2 x 8-1/8"		3/4 x 5-3/8"	7/8 x 4-3/16"	1 x 8-1/4"
3/8 x 6-1/8"	1/2 x 10-1/8"		3/4 x 5-7/8"	7/8 x 5-3/16"	1 x 9-1/4"
	1/2 x 12-1/8"		3/4 x 6-3/16"	7/8 x 6-3/16"	1 x 10-1/4"

800-458-9353

www.hybrocosales.com