

CENTER LOCK NUT (Two-way Reversible)

- Standard materials: steel & stainless steel.
- Steel center lock nuts are typically zinc plated; other plating options available.
- Recommended to be used with screws and bolts made of similar materials.

| Size & Thread Diameter | | Width Across Flats | | | Width Across Corners | | Thickness | | |
|---------------------------|--------|--------------------|--------|-------|----------------------|-------|-----------|-------|-------|
| | | Basic | Max | Min | Max | Min | Basic | Max | Min |
| 8 | 0.1640 | 11/32 | 0.344 | 0.332 | 0.397 | 0.378 | 3/16 | 0.193 | 0.178 |
| 10 | 0.1900 | 3/8 | 0.375 | 0.362 | 0.433 | 0.413 | 13/64 | 0.203 | 0.187 |
| 1/4 | 0.2500 | 7/16 | 0.438 | 0.428 | 0.505 | 0.488 | 7/32 | 0.226 | 0.212 |
| 5/16 | 0.3125 | 1/2 | 0.500 | 0.489 | 0.577 | 0.557 | 17/64 | 0.273 | 0.258 |
| 3/8 | 0.3750 | 9/16 | 0.562 | 0.551 | 0.650 | 0.628 | 21/64 | 0.337 | 0.320 |
| 7/16 | 0.4375 | 11/16 | 0.688 | 0.675 | 0.794 | 0.768 | 3/8 | 0.385 | 0.365 |
| 1/2 | 0.5000 | 3/4 | 0.750 | 0.736 | 0.866 | 0.840 | 7/16 | 0.448 | 0.427 |
| 9/16 | 0.5625 | 7/8 | 0.8875 | 0.861 | 1.010 | 0.982 | 31/64 | 0.496 | 0.473 |
| 5/8 | 0.6250 | 15/16 | 0.938 | 0.922 | 1.083 | 1.051 | 35/64 | 0.559 | 0.535 |
| 3/4 | 0.7500 | 1-1/8 | 1.125 | 1.088 | 1.299 | 1.240 | 41/64 | 0.665 | 0.617 |
| 7/8 | 0.8750 | 1-5/16 | 1.312 | 1.269 | 1.516 | 1.447 | 3/4 | 0.776 | 0.724 |
| 1 | 1.0000 | 1-1/2 | 1.500 | 1.450 | 1.732 | 1.653 | 55/64 | 0.887 | 0.831 |

Michigan

400 N. Clinton St.
Stockbridge, MI 49285
Phone: 517-851-8757
Fax: 517-851-7722

Tennessee

3100 Ambrose Ave.
Nashville, TN 37207
Phone: 615-352-6701
Fax: 615-352-6722

Wisconsin

Milwaukee, WI 53220
Phone: 414-344-8034