



KNURLED RIVET NUTS

Standard Sizes

- Standard materials: steel, aluminum, and stainless steel.
- Standard plating: plain, zinc & cadmium.
- Low profile with a knurled body; Thin wall with a standard flange.

Standard Sizes							
Thread Size	Grip Range	Under Head Length (Open End)	Under Head Length (Closed End)	Head Diameter	Head Thickness	Body Diameter	Hole Size
		+/- 0.015	+/- 0.015	+/- 0.10	Nom	Max	Ref.
6-32	0.020-0.080	0.420	0.740	0.390	0.030	0.265	0.266
6-32	0.080-0.130	0.470	0.740	0.390	0.030	0.265	0.266
8-32	0.020-0.080	0.420	0.740	0.390	0.030	0.265	0.266
8-32	0.080-0.130	0.470	0.740	0.390	0.030	0.265	0.266
10-24	0.020-0.130	0.475	0.990	0.415	0.030	0.296	0.297
10-24	0.130-0.225	0.585	0.990	0.415	0.030	0.296	0.297
10-32	0.020-0.130	0.475	0.990	0.415	0.030	0.296	0.297
1/4-20	0.027-0.165	0.580	1.190	0.500	0.030	0.390	0.391
1/4-20	0.165-0.260	0.680	1.190	0.500	0.030	0.390	0.391
1/4-28	0.027-0.165	0.580	1.190	0.500	0.030	0.390	0.391
1/4-28	0.165-0.260	0.680	1.190	0.500	0.030	0.390	0.391
5/16-18	0.027-0.150	0.690	1.390	0.685	0.035	0.530	0.531
5/16-18	0.150-0.312	0.805	1.390	0.685	0.035	0.530	0.531
5/16-24	0.027-0.150	0.690	1.390	0.685	0.035	0.530	0.531
5/16-24	0.150-0.312	0.805	1.390	0.685	0.035	0.530	0.531
3/8-16	0.027-0.150	0.690	1.390	0.685	0.035	0.530	0.531
3/8-16	0.150-0.312	0.805	1.390	0.685	0.035	0.530	0.531
3/8-24	0.027-0.150	0.690	1.390	0.685	0.035	0.530	0.531
3/8-24	0.150-0.312	0.806	1.390	0.685	0.035	0.530	0.531
1/2-13	0.062-0.200	1.150	2.365	0.865	0.047	0.685	0.687
1/2-13	0.200-0.350	1.300	2.365	0.865	0.047	0.685	0.687
1/2-13	0.350-0.500	1.450	2.365	0.865	0.047	0.685	0.687

800-458-9353

www.hybrocosales.com